

UDX - 75C Interactive **LED** Display



High End Interactive Technology

CLASS ROOMS / TRAINING ROOMS / BOARD ROOMS







| '5 inch | | |
|---------|--|--|
| | | |

UDX-75C

| | UD | X-75C | | |
|---------------------|---|-------------------------------|---|--|
| Size | 75 inch | | | |
| DISPLAY | | AUDIO | | |
| Screen Type | D-LED | Speaker Type | Built-in Speaker | |
| pect Ratio | 16:9 | Output Power | 10 W X 2 | |
| splay Area | 1649.664 (H) x 927.936 (V) mm | POWER | | |
| solution | 3840(H) × 2160(V) | Power Requirements | 100-240V ~ 50/60Hz | |
| sponse Time | 8ms | Standby Power | ≤0.5W | |
| freshing Frequency | 60Hz | Overall Power (nominal power) | 350 W | |
| isplay Color | 1.07B (10bit) | PC MODULE (Optional) | | |
| ixel Pitch | 0.4296 x 0.4296 mm | Туре | Detachable PC module | |
| rightness | 350 cd/m ² | Model | CT-22 series | |
| ontrast Ratio (Typ) | 1200 : 1 | CPU | Intel® Core™ i5 / i7 optional | |
| ewing Angle | 178° (H/V) | RAM | 4 GB / 8 GB* | |
| e Time | 50,000 Hours | SSD (optional) | 128 GB / 256 GB* | |
| OUCH SYSTEM | | Graphics | Integrated Intel® HD Graphics | |
| ensing Type | Infrared recognition | OPS Type | JAE 80 PIN Connector | |
| ystem | Windows 7/ 8/ 10 / Linux / Mac / Android / Chrome | Sound Card | Integrated High Definition Audio Stereo | |
| ouch point | 10 points writing & 20 points touch | Networking | 10/100/1000M | |
| linimum object size | ФЗmm | WiFi | 802.11 ac(2.4 GHz/ 5 GHz) | |
| sponse Time | <10ms | Operating System | Windows 10 | |
| curacy | 2 mm | Bluetooth | 4.2 | |
| mmunication Mode | Full-speed USB | USB 3.1/ USB 3.0 / USB 2.0 | 2/1/1 | |
| erface | USB | LAN (RJ45) | 1 | |
| rface Hardness | Toughened Glass with Level 7 of Mohs Standard | HDMI Output | 1 | |
| utput Cordinates | 32767 x 32767 | Line Out | 1 | |
| DISPLAY CONNECTORS | | Mic In | 1 | |
| IDMI IN | 3 | PHYSICAL SPECIFICATIO | PHYSICAL SPECIFICATIONS | |
| /GA IN | 1 | Dimension (L x H x D) | 1710 x 1020 x 87 mm | |
| C- Audio IN | 1 | Dimension (package) L x W x H | 1860 x 280 x 1140 mm | |
| arphone Output | 1 | Net Weight | 53.1 kg | |
| SB 2.0 | 3 (including 2 USB ports in front) | Gross Weight | 69.85 kg | |
| SB 3.0 | 3 | VESA | 600 x 400mm | |
| SB Touch Output | 2 | ENVIRONMENTAL COND | ITIONS | |
| PDIF | 1 | Operating Temperature | 0°C - 40°C | |
| \$232 | 1 | Operating Humidity | 10% - 90% | |
| an Port (RJ45) | 1 | Storage Temperature | -20°C - 60°C | |
| NDROID SYSTEM | | Storage Humidity | 10% - 90% | |
| system Version | Android 8.0 | | | |
| CPU | Dual Core A73 + Dual Core A53 | | | |
| GPU | Dual Core Mali G51 | | | |
| AM | 3 GB | | | |
| | | | | |

 * Model subject to availability in your region.

SPECKTRON

For, more information contact:

info@specktron.com | www.specktron.com