



I-Series Slate for Linux

Touchscreen Computer



Linux Debian 10



Compact Form Factor



**Enterprise-Grade
Support**

Product Overview

Elo's I-Series Slate delivers a powerful 15.6-inch Full HD interactive system, complete with Linux Debian 10 OS, powerful Rockchip processor and an I/O hub. Built to be one of the thinnest commercial-grade fixed tablet form factors, the I-Series Slate delivers a stunning design, enhanced durability, increased touch accuracy and brilliant display clarity.

With decades of development and customizations made to support global enterprise customers, Elo's Linux-based platform offers Linux device drivers, uniform SDKs, a constantly growing set of tools and an expansive lineup across sizes and form factors.

**Create a sleek point of sale system by
pairing with the Z10 & Z30 POS Stands**

**Easily mount the I-Series Slate with the
built-in 75 mm VESA mount**

**Elo's Linux-based platform offers
device drivers, uniform SDKs, and
a constantly growing set of tools**

I-Series Slate for Linux

Specifications	
Bezel Color	Dark Grey Metallic
Diagonal Size	15.6" (396.24mm)
Operating System	Linux Debian 10
Processor	Rockchip RK3399
Memory	4GB
Storage	32GB
I/O Ports	DC Input, 4 x USB-A 3.0 (900mA), RJ45 Ethernet LAN (Gigabit)
Display Head Interface	USB-C Connector Supports USB 2.0/3.0, DP output (Requires 20V/20W USB-C Power Delivery 2.0 if not using IO Hub for power)
Wireless	802.11a/b/g/n/ac + Bluetooth 5.0
Webcam	5MP, Max Resolution: 1920x1080 30fps, Auto Focus
Speakers	2x 1W
Audio	1x built-in Analog Microphone
Active Display Area	13.55" x 7.62" / 344 mm x 194 mm
Resolution	1920 x 1080 @ 60Hz
Touch Technology	TouchPro® PCAP (Projected Capacitive) - up to 10 touches
Aspect Ratio	16:9
Number of Colors	8-bit (16.7M)
Brightness	LCD Panel: 350 nits; PCAP: 280 nits
Response Time	20 ms
Viewing Angle	Horizontal: ±85° or 170° total / Vertical: ±85° or 170° total
Contract Ratio	1000:1
Power	AC input voltage: 100-240 VAC; Input frequency: 50-60 Hz
Power Consumption	On: 9.32W; Off: 0.4W; Sleep: 4.84W
Real-Time Clock	Lithium coin cell battery
Dimensions (W x D x H)	14.6" x 8.74" x 0.55" / 370.8 mm x 221.8 mm x 13.95 mm
Shipping Dimensions	17.44" x 12.20" x 6.14" / 443 mm x 310 mm x 156 mm
Weight	3.3 lbs / 1.5 kg
Shipping Weight	7.61 lbs / 3.45 kg
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 122°F (-20°C to 50°C)
Humidity	Operating: 20%-80%; Storage: 5%-95%
Mounting Options	VESA 75mm
MTBF	50,000 hours
Sealing	Touchscreen optically bonded to LCD
Warranty	2 years standard
Extended Warranty	3 yr: E819394; 4 yr: E819598; 5 yr: E819795 3 yr + ADP: E130329; 4 yr + ADP: E130530; 5 yr + ADP: E130719 2 yr + AUR: E819985; 3 yr + AUR: E820186; 4 yr + AUR: E820388; 5 yr + AUR: E820582 2 yr + AUR + ADP: E131490; 3 yr + AUR + ADP: E131674; 4 yr + AUR + ADP: E131859; 5 yr + AUR + ADP: E132053
Regulatory Approvals	UL/cUL (US); FCC (US); IC (Canada); CE (Europe); CB (International); VCCI, MIC (Japan); RCM (Australia)
What's in the Box	I-Series Slate, IO Hub, NA Power Cable, EU Power Cable, 4 x M4x6 mm flathead screws, 4 x M4x6 mm panhead screws, Power Brick 65W (E153026), QIG

Ordering Information

Part Number	Size	Processor	Color	Memory	Storage
E240416	15.6-inch	Rockchip RK3399	Dark Grey Metallic	4GB	32GB

Learn more about Elo at [EloTouch.com](https://www.elotouch.com).

Americas

Tel +1 408 597 8000
elosales.na@elotouch.com

Europe (EMEA)

Tel +32 16 930 136
EMEA.Sales@elotouch.com

Asia Pacific

Tel +86 (21) 3329 1385
EloAsia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2023 Elo Touch Solutions, Inc. All rights reserved. 23054AES00175

