




Screen size:  
13" - 34"



Max load:  
37 7/8 lbs



VESA:  
75x75 - 100x100 mm



Height adjustment:  
0"-1"

|                                      |                          |
|--------------------------------------|--------------------------|
| Made of                              | SPCC cold rolled steel   |
| Max. load of monitors/TVs            | 37 7/8 lbs               |
| VESA                                 | 75x75, 100x100 mm        |
| Screen size (min)                    | 13"                      |
| Screen size (max)                    | 34"                      |
| Number of screens                    | 2                        |
| Wall distance (min)                  | 3.52"                    |
| Wall distance (max)                  | 3.52"                    |
| Height adjustment (min)              | 0"                       |
| Height adjustment (max)              | 1"                       |
| Upward tilt angle (max)              | 45°                      |
| Downward tilt angle (max)            | 45°                      |
| Angle of rotation (range)            | 360°                     |
| Warranty                             | 5 years                  |
| Overall dimensions complete          | 39x28x90.5               |
| Dimensions of the individual package | 1 7/8" x 1 7/8" x 0 7/8" |
| Overall dimensions of the group pack | 2 x 1 x 1 1/4 inch       |
| Individual package volume            | 3.7 ft³                  |
| Gross weight individual              | 8 7/8 lbs                |
| Group gross weight                   | 57 7/8 lbs               |
| Number in group                      | 3 item(s)                |
| Number of individual per pallet      | 3                        |
| Number of groups per pallet          | 30                       |

ONKRON mounting solutions:

- Are suitable for continuous 24/7 use when installed and used in accordance with the applicable product documentation, installation instructions, and load specifications;
- Are intended for professional and commercial installations;
- Are designed to support secure and reliable installation of compatible displays in public environments;
- Comply with standard safety, installation, and mechanical requirements applicable to professional display mounting solutions;
- May be used in high-traffic public spaces, provided that installation is performed by qualified personnel and in accordance with all applicable local regulations, safety standards, and project requirements.